

IN THE DRAWINGS:

Please approve the accompanying Request For Approval Of Drawing Changes.

IN THE CLAIMS:

Please amend Claims 7, 8, 14, 15, 19 and 26 as shown in the attached Appendix, and add new Claims 27 to 30 as shown below. The claims, as pending in the subject application, read as follows:

1. (Not Amended From Previous Version) An image sensing device comprising:

light source means;

a recording member on which an image is formed and conveyed in one direction;

illumination means for causing a light beam emitted from said light source means to obliquely illuminate said recording member; and

imaging means for condensing specularly reflected light from the image on said recording member and causing the reflected light to travel to a surface of light receiving means, said image sensing device obtaining positional information of the image on said recording member on the basis of a signal obtained by said light receiving means,

wherein when the amount of displacement of the recording member in a vertical direction during conveyance of said recording member is d , an angle between the optical axis of said imaging means and a normal to said recording member is θ (degrees),

and resolution of the image formed on said recording member is R (dpi), the components are set so that

$d \cdot \tan \theta < (25.4/R) \times 1000$ is satisfied.

2. (Not Amended From Previous Version) A device according to claim 1, wherein the angle θ (degrees) satisfies

$$5^\circ < \theta < 35^\circ.$$

3. (Not Amended From Previous Version) A device according to claim 1, wherein said light source means comprises an LED light source, and said illumination means includes an illumination lens for condensing a light beam from said LED light source and causing the light beam to travel to said recording member.

4. (Not Amended From Previous Version) A device according to claim 1, wherein said imaging means includes an imaging lens for forming, on a surface of said light receiving means, an image on said recording member.

5. (Not Amended From Previous Version) A device according to claim 1, further comprising an imaging lens for forming, the image on the recording member onto said light receiving means, wherein when imaging magnification of said imaging lens is assumed to be β ,

$$0.75 < |\beta| < 1.25 \text{ is satisfied.}$$

6. (Not Amended From Previous Version) A device according to claim 1,
wherein the angle θ (degrees) satisfies

$$25^\circ < \theta < 35^\circ.$$

7. (Amended) An image forming apparatus including an image sensing
device according to claim 1, wherein said image forming apparatus includes a plurality of
image bearing members and forms a color image by using said image sensing device.

8. (Amended) An image sensing device comprising:

light source means;

illumination means for irradiating, with a light beam from said light source
means, a recording member on which an image is formed; and

imaging means for forming, onto a surface of a light receiving means, the
image on said recording member, said image sensing device detecting the image on the
recording member on the basis of a signal obtained by said light receiving means,

wherein when said recording member has a specular reflection surface, a
stop is provided to a position to be substantially optically conjugate with the light emitting
point of said light source means.

9. (Not Amended From Previous Version) A device according to claim 8,
wherein when the imaging magnification at which the light emitting point of said light
source is imaged at the conjugate position is assumed to be β ,

$$1 < |\beta| < 7 \text{ is satisfied.}$$

A1
Q2

10. (Not Amended From Previous Version) A device according to claim 8, wherein the aperture of the stop has a size substantially equal to or smaller than the size of the image of the light emitting point of said light source means.

Sub
P21

11. (Not Amended From Previous Version) A device according claim 8, wherein the stop is disposed between said imaging means and said light receiving means.

12. (Not Amended From Previous Version) A device according to claim 8, wherein said light receiving means detects the image formed on said recording member to obtain positional information of the image.

13. (Not Amended From Previous Version) A device according to claim 8, wherein said light receiving means detects density of the image formed on said recording member.

14. (Amended) An image forming apparatus including an image sensing device according to claim 8, wherein said image forming apparatus forms a color image by using said image sensing device, and

wherein said image forming apparatus includes a plurality of image bearing members.

MA
15. (Amended) An image sensing device comprising:

light source means;

illumination means including an irradiation lens for irradiating, with a light beam from said light source means, a recording medium on which an image is formed; and

Sub BA
imaging means including an imaging lens for forming, onto a surface of a light receiving means, the image on the recording medium, said image sensing device detecting the image on said recording member on the basis of a signal obtained by said light receiving means,

wherein at least one of the surface of said irradiation lens and said imaging lens on said recording member side is flat.

16. (Not Amended From Previous Version) A device according to claim 15, wherein at least one of said irradiation lens and said imaging lens has at least one rotationally symmetrical aspherical surface.

17. (Not Amended From Previous Version) A device according to claim 15, wherein at least one of said irradiation lens and said imaging lens has at least one anamorphic surface.

18. (Not Amended From Previous Version) A device according to claim 15, wherein at least one surface of said irradiation lens and said imaging lens is inclined relative to a surface normal to said recording member.

Amend

19. (Amended) A device according to claim 15, wherein said irradiation lens and said imaging lens are formed integrally with each other and are made of a same material.

*Sub
pal*

20. (Not Amended From Previous Version) A device according to claim 15, wherein an optical axis of said irradiation lens and an optical axis of said imaging lens have equal angles formed in opposite directions from a surface normal to said recording member.

21. (Not Amended From Previous Version) A device according to claim 15, wherein said light source means is provided with a moving mechanism capable of displacing to an arbitrary position.

22. (Not Amended From Previous Version) A device according to claim 15, wherein said light receiving means is provided with a moving mechanism capable of displacing to an arbitrary position.

23. (Not Amended From Previous Version) A device according to claim 15, wherein said imaging means has a stop, and a light emitting surface of said light receiving means and the stop are made substantially conjugate with each other when a surface of said recording member is a specular reflection surface.

24. (Not Amended From Previous Version) A device according to claim 15,
wherein said light receiving means detects the image formed on said recording member to
obtain positional information of the image.

25. (Not Amended From Previous Version) A device according to claim 15,
wherein said light receiving means detects density of the image formed on said recording
member.

26. (Amended) An image forming apparatus including an image sensing
device according to claim 15, wherein said image forming apparatus forms a color image
by using said image sensing device, and
wherein said image forming apparatus includes a plurality of image bearing
members.

27. (New) An image sensing device comprising:
light source means;
illumination means for irradiating, with a light beam from said light source
means, a recording medium on which an image is formed; and
imaging means for forming, onto a surface of a light receiving means, the
image on the recording medium, said image sensing device detecting the image on said
recording medium on the basis of a signal obtained by said light receiving means,
wherein said light source means is provided with a moving mechanism
capable of displacing to an arbitrary position.

28. (New) An image sensing device according to claim 27, which is provided in an image forming apparatus that forms a color image by using said image sensing device, and

wherein said image forming apparatus includes a plurality of image bearing members.

29. (New) An image sensing device comprising:

light source means;

illumination means for irradiating, with a light beam from said light source

means, a recording medium on which an image is formed; and

imaging means for forming, onto a surface of a light receiving means, the image on the recording medium, said image sensing device detecting the image on said recording member on the basis of a signal obtained by said light receiving means,

wherein said light receiving means is provided with a moving mechanism capable of displacing to an arbitrary position.

30. (New) An image sensing device according to claim 29, which is provided in an image forming apparatus that forms a color image by using said image sensing device, and

wherein said image forming apparatus includes a plurality of image bearing members.